



P. PSYLLAKIS & Co. CAVOMIT O.E.  
HOT STAMPING SYSTEMS  
7, Dimokratias Ave., 134 51 Kamatero, Greece  
Tel: +30-210-2381949 / 210-2319627  
E-mail: [cavomit5@gmail.com](mailto:cavomit5@gmail.com)  
Website: [www.cavomit.gr](http://www.cavomit.gr)

**(ST.50X70) Nantong Lihua China Cutting Machine  
For Mounting Cavomit MDL-122 Mechanical Hot Stamping System**

**(ST.50X70)** The mechanical **(MDL-122)** Hot Stamping system Mounting for **(Nantong Lihua China)** one until two mechanic Foil Pulls Is manufactured at the **Cavomit** factory.

It is placed on a machine **(Nantong Lihua China)** cutting machine or on any other machine that is fully repaired and maintained and carries a guarantee from the **Cavomit** company.

You place the new model Hot Stamping system Mechanical or Electronic for mounting in our **Cavomit** company.



**Hot Plate:**

Single-piece hot plate, 16 mm thickness, with max. area coverage, made of high conductivity light alloy. The hot plate has a temperature insulation from the machine body for increased energy savings and optimal heat allocation.

The hot plate is permanently placed in a printing chase allowing easy replacement with cutting/creasing chase or spare hot-plate for fast changeover of various printing jobs.

The required precision of the printing temperature is acquired through 3 until 18 reliable, parallel resistances unevenly allocated all across the width of the plate in 1 until 6 precision temperature control zones, controlled by an 1 until 6 electronic temperature instruments.

<b>Technical specifications (ST 50X70) for Cutting &amp; Hot Stamping machine</b>	
<b>1. Paper parameters</b>	
Paper size max	30X40 / 35X50 / 50X70 / 70X100 cm
Paper size min	Depending on the model
Paper sheet thickness max.	600 grm
Max. blocking area	Depending on the model
<b>2. Operation control parameters</b>	
Control system	Mechanical
Foil-pulls	1
Pull step accuracy	0.01 mm
Foil-pull cylinders	1
Foil rewind units	1
Counters	1
<b>3. Foil parameters</b>	
Foil roll width max	Depending on the model
Foil roll width min	15 mm
Distance between rolls (min)	2 mm on same bar axis
Roll core diameter	16 or 25 mm on same bar axis
External diameter of foil roll feed	Depending on the model
External diameter of used foil	140 mm on 25 mm core
<b>4. Printing parameters</b>	
Blocking speed	Depending on the model
Alternative uses	Cutting, creasing, embossing, punching
<b>5. Hot plate parameters</b>	
Hot plate	Single-piece, honeycomb hot plate
Heating zones	1 for optimal temperature allocation
Temperature regulation	1 temperature instrument
Resistances	Parallel 3
Printing die height	1.63 2.50 3.00 7.00 mm
Die mounting on hot plate	With micrometric adjustable mounts
Roll width	Depending on the model
<b>7. Physical parameters</b>	
Length	Depending on the model
Width	Depending on the model
Height	Depending on the model
Weight	Depending on the model
Motor type	Depending on the model
Total connection capacity	Depending on the model
Voltage	230 / 250 / 380/460V, 50 Hz